

Bear Ridge Speedway 2020 Limited Late Models

REFER TO TRACK GENERAL RULES FOR NON-DIVISION SPECIFIC RULES

Any 1955 to present American made production car with 100" Minimum wheelbase. No four wheel drive or front wheel drive cars. Max engine set back—#1 spark plug in line with upper ball joint.

BODIES:

- ⌘ Any stock steel, after market, or home made.
- ⌘ Roof must be flat
- ⌘ Rear spoiler 8" maximum
- ⌘ Must have front bumper with cover and outside chain for towing
- ⌘ Bumpers must remain in stock location:
- ⌘ Side rails optional MUST BE TIGHT TO BODY
- ⌘ Added weight must be painted white with your car number on it.

SUSPENSIONS:

- ⌘ Leafs allowed in rear
- ⌘ A frames must be in stock location with any mount
- ⌘ **FRONT** coilovers allowed (2 ½ in. spring min.)
- ⌘ Tie rods and steering arms may use heim joints
- ⌘ 4 shocks maximum price \$150.00 per shock, may mount outside stock location
- ⌘ Jack bolts allowed
- ⌘ NO torque arms, bird cages, rubber donuts, or spring rods allowed.

⌘ **NO BIRD CAGES NO BIRD CAGES ABSOLUTELY NO BIRD CAGES ALLOWED**

DRIVE TRAIN:

- ⌘ Automatic transmissions ALLOWED. Fly wheel, clutch and pressure plate must be stock appearing.
- ⌘ 3 or 4 speed allowed.
- ⌘ Steel bell housing or must have scatter shield
- ⌘ Any rear end allowed. Quick change allowed

ENGINE:

- ⌘ Chevy 350 no aluminum except intake
- ⌘ Cam lift at valve .500
- ⌘ 602 crate allowed
- ⌘ Headers allowed street type only no 180's
- ⌘ No dry sump systems
- ⌘ Option 1: #1 sparkplug must be in line with upper ball joint 2600 pounds after feature
- ⌘ Option 2: 6" engine set back 2700 pounds after feature

INTAKE MANIFOLD:

- ⌘ Any intake
- ⌘ Stock Holley 500 CFM 2 barrel or equivalent
- ⌘ 1" adapter plate maximum
- ⌘ 4 barrel allowed on 602 crate motors ONLY

HEADS:

- ⌘ 10.5 compression maximum allowed.
- ⌘ Cast iron heads only. No angle plug
- ⌘ 1.94 intake 1.60 exhaust allowed.
- ⌘ Roller rockers or roller tip rockers allowed.

IGNITION:

- ⌘ Distributer H.E.I. only

ROLL CAGE:

- ⌘ A)1 ½ IN MINIMUM FULL CAGE MANDATORY

FUEL CELL

- ⌘ Mandatory, must be secured in trunk
- ⌘ Must have foam and flapper under cap

WHEELS AND TIRES:

- ⌘ Steel only 8" or 10" allowed bead locks allowed. 1" lug nuts required.
- ⌘ Track tire only allowed

WEIGHT

- ⌘ Option 1: #1 sparkplug must be in line with upper ball joint 2600 pounds after feature
- ⌘ Option 2: 6" engine set back 2700 pounds after feature

INTERPRETATION OF RULES BY AN OFFICIAL IS FINAL. THE MANAGEMENT RESERVES THE RIGHT TO CHANGE ANY RULE OR RULES IF THEY FEEL IT IS NECESSARY, AND REFUSE ANY PROTEST IF THEY FEEL IT IS UNNECESSARY AND BEING USED FOR HARASSING REASONS. ALL FINES AND/OR SUSPENSIONS WILL BE IN EFFECT AT ALL BEAR RIDGE SPEEDWAY EVENTS.

THE INTERPRETATION AND INVOKING OF THE RULES PUBLISHED HERIN SHALL BE DETERMINED BY BEAR RIDGE SPEEDWAY OFFICIALS ONLY IN THEIR PROFESSIONAL DISCRETION.

BEAR RIDGE SPEEDWAY INC.

OWNED AND OPERATED BY

APRIL MAY and C.V. ELMS

FAX 603/787-2490

TRACK PHONE 802/222-4052

brsdirt@charter.net

WWW.BEARRIDGESPEEDWAY.COM