

Bear Ridge Speedway 2022 Late Models

REFER TO TRACK GENERAL RULES FOR NON-DIVISION SPECIFIC RULES

Any 1955 to present American made production car with 100" Minimum wheelbase. No four wheel drive or front wheel drive cars.

BODIES:

- ⌘ Any stock steel, after market, or home made.
- ⌘ Roof must be flat
- ⌘ Rear spoiler 8" maximum
- ⌘ Must have front bumper with cover and outside chain for towing
- ⌘ Bumpers must remain in stock location:
- ⌘ Side rails optional MUST BE TIGHT TO BODY
- ⌘ Added weight must be painted white with your car number on it.
 - NO WEIGHT OUTSIDE OF FRAME

SUSPENSIONS:

- ⌘ Leafs allowed in rear
- ⌘ A frames must be in stock location with any mount
- ⌘ **FRONT** coilovers allowed (2 ½ in. spring min.)
- ⌘ Tie rods and steering arms may use heim joints
- ⌘ Jack bolts allowed
- ⌘ "4 Link Cars Allowed 2600 LBS MINIMUM"
 - ONE SHOCK PER WHEEL

DRIVE TRAIN:

- ⌘ Automatic transmissions ALLOWED. Fly wheel, clutch and pressure plate must be stock appearing.
- ⌘ 3 or 4 speed allowed.
- ⌘ Steel bell housing or must have scatter shield
- ⌘ Any rear end allowed. Quick change allowed

ENGINE:

- ⌘ Chevy 350 no aluminum except intake
 - ALL OTHERS CALL THE TRACK
- ⌘ Cam lift at valve .500
- ⌘ 602 crate allowed
- ⌘ Headers allowed street type only no 180's
 - MUFFLERS MANDATORY
- ⌘ No dry sump systems
- ⌘ Option 1: #1 sparkplug must be in line with upper ball joint 2300 LBS after feature
- ⌘ Option 2: 6" engine set back 2600 LBS after feature

INTAKE MANIFOLD:

- ⌘ Any intake
- ⌘ Stock Holley 500 CFM 2 barrel or equivalent
 - CHOKE HORN MUST BE IN PLACE
- ⌘ 1" adapter plate maximum open hole NO SUPER SUCKERS
- ⌘ 4 barrel allowed on 602 crate motors only NO SUPER SUCKERS

HEADS:

- ⌘ 10.0:1 compression maximum allowed.
- ⌘ Cast iron heads only. No angle plug
- ⌘ 1.94 intake 1.60 exhaust allowed.
- ⌘ Roller rockers or roller tip rockers allowed.

IGNITION:

- ⌘ Distributer H.E.I. only

ROLL CAGE:

- ⌘ A)1 ½ IN MINIMUM FULL CAGE MANDATORY

FUEL CELL

- ⌘ Mandatory, must be secured in trunk
- ⌘ Must have foam and flapper under cap

WHEELS AND TIRES:

- ⌘ Steel only 8" or 10" allowed bead locks allowed. 1" lug nuts required.
- ⌘ TTRACK TIRE ONLY NO OTHERS ALLOWED

WEIGHT

- ⌘ Option 1: #1 sparkplug must be in line with upper ball joint 2300 LBS after feature
- ⌘ Option 2: 6" engine set back 2600 LBS after feature
- ⌘ 4 Link Cars 2600 LBS MINIMUM

INTERPRETATION OF RULES BY AN OFFICIAL IS FINAL. THE MANAGEMENT RESERVES THE RIGHT TO CHANGE ANY RULE OR RULES IF THEY FEEL IT IS NECESSARY AND REFUSE ANY PROTEST IF THEY FEEL IT IS UNNECESSARY AND BEING USED FOR HARASSING REASONS. ALL FINES AND/OR SUSPENSIONS WILL BE IN EFFECT AT ALL BEAR RIDGE SPEEDWAY EVENTS.

THE INTERPRETATION AND INVOKING OF THE RULES PUBLISHED HERIN SHALL BE DETERMINED BY BEAR RIDGE SPEEDWAY OFFICIALS ONLY IN THEIR PROFESSIONAL DISCRETION.

BEAR RIDGE SPEEDWAY INC.

OWNED AND OPERATED BY

APRIL MAY and C.V. ELMS

FAX 603/787-2490

TRACK PHONE 802/222-4052

brsdirt@charter.net

WWW.BEARRIDGESPEEDWAY.COM

UPDATED- 12/7/2021